



## **UniCrimp 100** **Crimping Machine**

- Rugged steel frame construction
- Simple design and easy operation
- Adjustable work light
- Integrated piece counter

CRIMP

# UniCrimp 100

## Concept

The UniCrimp 100 crimping machine terminates stripped wires up to 6 mm<sup>2</sup> (10 AWG). The machine accepts most industry-standard, mini-style applicators for crimping left side and rear-feed terminals.

## Options

- Pneumatic feed kit
- Quick-change applicator base plate

Technical Specifications	
Force	20 kN (2.2 tons)
Cross section range	Up to 6 mm <sup>2</sup> (10 AWG) (Material thickness up to 0.75 mm [0.03"] / Length of the crimping zone up to 6 mm [0.24"])
Stroke	40 mm (1.58")
Shut height	135.78 mm (5.346")
Press activation	Foot Pedal
Noise level	< 70 dB (A)
Power	120 VAC, 60 Hz
Dimensions (L x W x H)	380 x 400 x 710 mm (15.0 x 15.8 x 28.0")
Weight	55 kg (121 lbs.)
CE – conformity	The UniCrimp 100 fully complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.
Important note	Schleuniger recommends that wire samples be submitted in cases where there is doubt as to the processing capabilities of a particular machine.