



PullTester 320 **Pull Testing Machine**

- Triple range for the best accuracy over the widest range of wires
- 4 selectable pulling rates to comply with common test requirements
- Speed-controlled motor for consistent pull rates throughout the measuring range
- Fully integrated into CrimpCenter EASY software to save time

QUALITY ASSURANCE

PullTester 320

Concept

Schleuniger's PullTester 320 is a motorized device for use with Schleuniger CrimpCenter automatic crimping machines to measure pull-test forces of wire terminations. Pull-test values are critical parameters for quality control and assurance. This versatile machine has three measuring ranges, which are individually calibrated. Multiple pulling ranges offer a higher accuracy over the entire device range than single-range devices. The standard measuring ranges are 100 N, 200 N and 1,000 N (22.5 lbf, 45 lbf, and 220 lbf). The PullTester 320, with its triple-range capability, ensures the highest accuracy over the widest range of applications. Hand actuated or pneumatic pull test devices can give inconsistent data depending on the operator or pull rate. Some standards specify that a test device must pull with a specific, constant rate. The Schleuniger PullTester 320 offers four selectable pulling rates consistent with the most common specifications. It is equipped with a speed-controlled motor, ensuring consistent pull rates throughout the complete measurement cycle resulting in repeatable and accurate data. Pull forces can be measured in pounds, Newtons or kiloponds. All necessary testing parameters are programmed via the CrimpCenter EASY software and saved with individual jobs for easy recall.

Processing Capabilities

The standard, 12-position terminal holder accommodates a wide variety of terminals to handle most applications. The machine will test pull forces up to 1,000 N (220 lbf.) and is especially suited for quality assurance in a production environment.

Technical Specifications	
Measurement range	0-100 N / 0-22 lbf / 0-10 Kp 0-200 N / 0-44 lbf / 0-20 Kp 0-1,000 N / 0-220 lbf / 0-100 Kp
Units of measure	N, Kp, lb.
Applied force accuracy	±0,2 % of measurement range
Operating voltage	24 VDC
Operating temperature range	0 - 50° C (32 - 120° F)
Maximum stroke	45 mm (1.70")
Pulling speed	25, 50, 100, High mm/min (0.98, 1.97, 3.94"/min. or high speed)
Pulling modes	Pull + Break: normal pull test until wire breaks
Interface	RS 232
Dimensions (L x W x H)	330 x 205 x 240 mm (13 x 8 x 9.5")
Weight	Approximately 7 kg (15 lbs.)
Protective class	IP 20
CE – conformity	The PullTester 320 fully complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.
Important note	Schleuniger recommends that wire samples be submitted in cases where there is doubt as to the processing capabilities of a particular machine.